

STEELMASTER SM-HBS370RN SERIES BANDSAW

Quality Made Bandsaws with Semi Automatic Standard and Hydraulic Clamping Option.

FEATURES

- double mitre cut to 45 and 60 degrees right and left sides.
- variable hydraulic down feed system for the automatic continuous lowering of the saw frame
- hydraulic vice clamping & auto beam return (SM-HBS370RNSAM)
- heavy duty cast iron frame ensuring rigidity and smooth cutting
- vibration free, low noise operation ensures clean cutting and high accuracy maintained
- stand and coolant system included
- deadman trigger switch
- blade tension gauge
- quick release vice system standard
- optional hydraulic vice clamping
- quick action mitre adjustment
- carbide blade guides
- 415 Volt operation
- CE compliant



UNIQUE FEATURES

"making ours unique!"



- Tungsten blade guides
- Blade Tension Gauge
- Safe Front Operating Panel

TECHNICAL DATA	(model)	SM-HBS370RN	SM-HBS370RNSAM
sku	(#)	15-0388	15-0389
cutting capacities ø (w x h)			
	90°	270	270
	60° (mm)	140 (R)	140 (R)
	45°	230 (R) 180(L)	230 (R) 180(L)
	90°	260	260
	60° (mm)	140 (R)	140 (R)
	45°	210 (R) 170(L)	210 (R) 170(L)
	90°	360 x 260	360 x 260
	60° (mm)	140 x 140	140 x 140
	45°	210 x 280	210 x 280
	90° (mm)	260/270	260/270
beam return	(type)	spring	hydraulic
blade size (l x w x t)	(mm)	2925 x 27 x 0.9	2925 x 27 x 0.9
vice clamping	(type)	manual	hydraulic
speed range / 415V	(m/min)	35 ~ 72	35 ~ 72
table working height	(mm)	940	940
motor power	(kw/V)	2.0 / 415	2.0 / 415
dimensions - (l x w x h)	(mm)	1930 x 970 x 1120	1930 x 970 x 1120
weight (nt)	(kg)	495	540
PRICE	(AUD)	\$	\$

EQUIPMENT & ACCESSORIES SUPPLIED

Standard blade fitted, machine stand, in-feed roller, length stop, blade tension gauge, trigger switch, toolkit & manual.

OPTIONAL ACCESSORIES - RONTGEN BI-METAL BANDSAW BLADES

SKU	MODEL TO SUIT	LENGTH X WIDTH X THICKNESS	PITCH	PRICE
15+0060	SM-HBS370RN	2925 x 27 x 0.9	6/10 tpi	\$
15+0059	SM-HBS370RN	2925 x 27 x 0.9	8/12 tpi	\$
15+0061	SM-HBS370RN	2925 x 27 x 0.9	10/14 tpi	\$

The Rontgen bi-alfa cobalt Bandsaw Blade has a high resistance to wear since a number of super hard special carbides are distributed particularly evenly in the optimum hardened and tempered structure of the tooth tips. Its firm embedding into a temperature stable martensitic environment and the high cobalt content ensure very good thermal resistance to wear. The support band made of alloyed tempering steel with approx. 4% chromium is the warranty for outstanding fatigue strength under reversed bending stresses.



3 ph /415 volt machinery do not come fitted with plugs as standard. GST is NOT included in the listed prices



ASSET PLANT & MACHINERY PTY LTD
8 Capital Drive, Dandenong VIC 3175

Tel : (03) 8710-8088
Fax : (03) 8710-8044

Web : www.assetplant.com.au
Email : sales@assetplant.com.au