

# STEELMASTER SM-HBS530SAM SERIES BANDSAW

Quality Made Bandsaws with Semi Automatic Standard and Hydraulic Clamping Option.

## FEATURES

- double mitre cut to 45 and 60 degrees right and left sides.
- variable hydraulic down feed system for the automatic continuous lowering of the saw frame
- hydraulic vice clamping & auto beam return (SM-HBS370RNSAM)
- heavy duty cast iron frame ensuring rigidity and smooth cutting
- vibration free, low noise operation ensures clean cutting and high accuracy maintained
- stand and coolant system included
- deadman trigger switch
- blade tension gauge
- quick release vice system standard
- optional hydraulic vice clamping
- quick action mitre adjustment
- carbide blade guides
- 415 Volt operation
- CE compliant



## UNIQUE FEATURES

"making ours unique!"



- 34mm Wide Blade
- Tungsten Blade Guides
- Hydraulic Vice Clamp
- Auto Beam Return

TECHNICAL DATA		(model)	SM-HBS370RNSAM
sku		(#)	15-0393
cutting capacities ø (w x h)			
○	90°		355
	60°	(mm)	240
	45°		355
□	90°		330
	60°	(mm)	170
	45°		290
▭	90°		330 x 530
	60°	(mm)	170 x 240
	45°		290 x 360
■●	90°	(mm)	355/330
beam return	(type)		hydraulic
blade size (l x w x t)	(mm)		3770 x 34 x 0.9
vice clamping	(type)		hydraulic
speed range / 415V	(m/min)		20 ~ 80
table working height	(mm)		940
motor power	(kw/V)		3.0Kw / 415
dimensions - (l x w x h)	(mm)		2180 x 970 x 1130
weight (nt)	(kg)		855
<b>PRICE</b>	<b>(AUD)</b>		<b>\$</b>

## EQUIPMENT & ACCESSORIES SUPPLIED

Standard blade fitted, machine stand, in-feed roller, length stop, blade tension gauge, trigger switch, toolkit & manual.

OPTIONAL ACCESSORIES - RONTGEN BI-METAL BANDSAW BLADES				
SKU	MODEL TO SUIT	LENGTH x WIDTH x THICKNESS	PITCH	PRICE
15+0195	SM-HBS370SAM	3770 x 34 x 0.9	6/10 tpi	\$
15+0196	SM-HBS370SAM	3770 x 34 x 0.9	8/12 tpi	\$
15+0197	SM-HBS370SAM	3770 x 34 x 0.9	10/14 tpi	\$

The BICHAMP bi-alfa cobalt Bandsaw Blade has a high resistance to wear since a number of super hard special carbides are distributed particularly evenly in the optimum hardened and tempered structure of the tooth tips. Its firm embedding into a temperature stable martensitic environment and the high cobalt content ensure very good thermal resistance to wear. The support band made of alloyed tempering steel with approx. 4% chromium is the warranty for outstanding fatigue strength under reversed bending stresses.



3 ph /415 volt machinery do not come fitted with plugs as standard. GST is NOT included in the listed prices



ASSET PLANT & MACHINERY PTY LTD  
8 Capital Drive, Dandenong VIC 3175

Tel : (03) 8710-8088  
Fax : (03) 8710-8044

Web : [www.assetplant.com](http://www.assetplant.com)  
Email : [sales@assetplant.com](mailto:sales@assetplant.com)