CLEARMASTER FUME EXTRACTION SYSTEM

A workplace must for all CNC Plasma Laser Profilers









A workplace must for all CNC Plasma Laser Profilers – suits table size up to 2000mm x 4000mm

Simply power up and connect your ducting for a cleaner, safer workplace.

Fitted off with spark arrestors and providing a clean, safe, healthy work environment.

TECHNICAL DATA	(model)	SM-DR-3000	SM-PA-6000CT	SM-SHF-30
sku	(#)	21-0805	21-0806	21-0807
extraction type	(type)	Spark, Smoke, Fume, Dust	Spark, Smoke, Fume, Dust	Spark, Small Parts, Grinding, Polishing, Smoke, Fume, Dust,
table area	(mm)		4000 x 2000	800 x 670
air volume	(m3/Hr)	3000	6000	3600
filter	(type)	PTFE Coated Folded Cartridge	PTFE Coated Folded Cartridge	PTFE Coated Folded Cartridge
compressed air	(Mpa)	0.5 ~ 0.6	0.5 ~ 0.6	0.5 ~ 0.6
solenoid valves	(state)	2 off	2 off	2 off
power	(Kw/v)	3 / 415	7.5 / 415	3 / 415
weight	(kg)	280	220	280
dimensions (I x w x h)	(mm)	920 x 700 x 1820	954 x 1620 x 2275	800 x 1100 x 1900
PRICE	(AUD)	\$	\$	\$

Web: www.assetplant.com.au Email: sales@assetplant.com.au